

11/06/00
JC949 U.S. PTO

11-07-00
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: RAMSAY ET AL.
Docket: 13095.1USU1
Title: SYSTEM AND METHOD FOR IMAGE PROCESSING

JC944 U.S. PTO
09/707144
11/06/00

CERTIFICATE UNDER 37 CFR 1.10

'Express Mail' mailing label number: EL 649974454 US

Date of Deposit: November 6, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

By: Chatia Lambert
Name: Chatia Lambert

BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

We are transmitting herewith the attached:

- ☒ Transmittal sheet, in duplicate, containing Certificate under 37 CFR 1.10.
- ☒ Utility Patent Application: Spec. 46 pgs; 118 claims; Abstract 1 pgs.
The fee has been calculated as shown below in the 'Claims as Filed' table.
- ☒ 10 sheets of informal drawings
- ☒ Assertion of Small Entity Status (1 page)
- ☒ An unsigned Combined Declaration and Power of Attorney
- ☒ A check in the amount of \$1437.00 to cover the Filing Fee
- ☒ Return postcard

CLAIMS AS FILED

Number of Claims Filed	In Excess of:	Number Extra	Rate	Fee
Basic Filing Fee				\$355.00
Total Claims				
118	- 20	= 98	x 9.00	= \$882.00
Independent Claims				
8	- 3	= 5	x 40.00	= \$200.00
MULTIPLE DEPENDENT CLAIM FEE				\$0.00
TOTAL FILING FEE				\$1437.00

Please charge any additional fees or credit overpayment to Deposit Account No. 13-2725. A duplicate of this sheet is enclosed.

MERCHANT & GOULD P.C.
P.O. Box 2903, Minneapolis, MN 55402-0903
(612) 332-5300

By: Min S. Xu
Name: Min S. Xu
Reg. No.: 39,536
Initials: AX/mas



23552

PATENT TRADEMARK OFFICE

(PTO TRANSMITTAL - NEW FILING)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: RAMSAY ET AL. Examiner: Unknown
Serial No.: Unknown Group Art Unit: Unknown
Filed: November 6, 2000 Docket No.: 13095.1USU1
Title: SYSTEM AND METHOD FOR IMAGE PROCESSING

1c944 U.S. PTO
09/707144
11/06/00

CERTIFICATE UNDER 37 CFR 1.10:

"Express Mail" mailing label number: EL 649974454 US
Date of Deposit: November 6, 2000

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to Assistant Commissioner for Patents, Washington, D.C. 20231.

By: Chatia Lambert
Name: Chatia Lambert

ASSERTION OF SMALL ENTITY STATUS

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

Applicant is a small entity as defined under 37 C.F.R. § 1.27, and hereby asserts a small entity status for the above-identified patent application pursuant to 37 C.F.R. § 1.27(c) for the purpose of paying small entity fees.

Respectfully submitted,

MERCHANT & GOULD P.C.
P. O. Box 2903
Minneapolis, MN 55402-0903
612/332-5300



By: Min S. Xu
Min S. Xu
Reg. No. 39,536
AX/mas

SYSTEM AND METHOD FOR IMAGE PROCESSING

RELATED APPLICATION

5 This application claims the benefit of Provisional Application, U.S. Serial No. 60/184,088, filed on February 22, 2000, entitled "SUPER JPEG BUILDER AND METHOD FOR IMAGE ENHANCEMENT", by Kenneth Richards, Thomas Ramsay, and Michael Wackerfuss.

TECHNICAL FIELD

10 The present invention relates to image processing, more particularly, to an image processing system and method for automatically processing images without operator's intervention.

BACKGROUND OF THE INVENTION

15 Considerable research and development have been conducted over the past few years in image processing fields, for example, image compression to reduce an image file size, or image enhancement to improve an image quality, etc.

 Typically, image data are large in size and often required to be compressed to a smaller size before they are stored and/or transmitted in media.

20 Various methods have been developed to compress an image file. For example, in U.S. Patent No. 5,426,512, a method of digital compression of images is disclosed. The

patented method uses a DCT transform coefficients yielded from a Discrete Cosine Transform (DCT) of all the blocks as well as other display and perceptual parameters to generate a quantization matrix which in turn yields a reproduced image having a low perceptual error. The patented method adapts or customizes the individual quantization
5 matrix to the image being compressed.

One of the problems associated with existing image compression methods is that these compression methods do not apply any pre-compression filtering to reduce image quality degradation as the compression is applied, e.g. sharpening of images, removing artifacts, etc. Under a high compression setting, an image generally
10 loses its image characteristics/attributes. Further, compression of images introduces artifacts. These methods of compression do not take into account for preparing the image prior to compression to reduce the visible artifacts so as to maximize the compression applied and retain visual qualities. Images that have been 1) previously compressed with an algorithm, for example, JPEG (Joint Photographic Expert Group);
15 2) having a dot pattern from being scanned; 3) GIF images that have dots because of their dithering or color pallet being limited to some number of colors, have varying degrees of artifacts dependent upon the compression applied.

Some existing image processing systems apply enhancement to original and previously compressed images to enhance the image quality. When automated, the
20 same enhancement parameters are applied to all images of the batch process such as contrast or brightness without taking into account for the individual qualities of each

image to be enhanced. Thus, these existing image enhancement systems may not enhance a batch processed image, but degrade the quality and/or visual characteristics of the image as viewed by a human. In addition, artifacts problems still remain.

Another problem that resides in conventional image enhancement systems is that the image processing requires an operator's intervention. Typically, an operator randomly chooses image processing parameters, such as sharpness, contrast percentage, etc., enhances an image based on the chosen parameters, and judges whether the enhanced image is acceptable. If not, different image processing parameters are chosen to enhance an original image. This process is time consuming. This process is more or less depending on operator's experience. U.S. Patent No. 5,694,484 has addressed these concerns and attempts to solve the problem. However, the system still requires an operator's intervention, even though it is minimized. For example, an operator needs to select image processing operations to process an input image. Further, as mentioned above, like many other existing image enhancement systems, this patented system does not enhance an image to a point that the image has quality and/or visual characteristics as viewed by a human and does not pre-process the image prior to compression so as to reduce image quality degradation or artifacts introduced by the compression method and thus allow a greater degree of compression to be applied while retaining visual qualities.

Furthermore, existing enhancement and compression methods do not take into account for image quality such as sharpness as the size of the image is reduced.

This is particularly true with thumbnail images where the amount of information that defines the image and its characteristics are very small. Thus, small images, such as thumbnails, have poor visual quality.

A further problem of conventional image enhancement systems is that an
5 input image must be loaded into a memory repeatedly for each multiple output desired.
This slows down the processing time and wastes many resources.

It is with respect to these and other considerations that the present invention has been made.

005074-10600

SUMMARY OF THE INVENTION

In accordance with this invention, the above and other problems were solved by providing an image processing system and method capable of automatically analyzing, classifying, enhancing, pre-compression processing, and compressing each of
5 a series of input images on-the-fly without operator's intervention in a wire and/or wireless transmission environment or embedded in a hardware, software, or firmware device, and outputting one or more enhanced images without re-analyzing, re-classifying, and re-enhancing the input image.

The present invention provides an image processing system and method
10 which automatically generates one or more highest quality images in given file sizes. Also, the present invention provides a system capable of processing a series of input images in a batch mode or in real time on-the-fly. Accordingly, the system in accordance with the principles of the present invention can function as a round-the-clock "professional image processing specialist" with speed and skill levels unmatched
15 by any human counterpart.

Further, the present invention provides a system and method which greatly improve high-contrast or over- or under-exposed pictures, images generated from document scanners or digital cameras, etc.

Furthermore, the present invention provides an image processing system
20 and method for generating enhanced and/or compressed images having a high compression to quality ratio, such as a JPEG image, and enhanced uncompressed

images, such as a BMP (Bitmap) or TIFF (.tif) image. For example, the system produces an image having quality and visual characteristics as viewed by a human including image brightness, contrast, and sharpness as compared with an original uncompressed image, while reducing the amount of memory required for storing the
5 file.

In one embodiment of the present invention, each input image is analyzed for its unique luminosity and/or color characteristics/attributes, classified, and enhanced to improve its visual qualities. The method includes automatically analyzing a luminosity histogram associated with a particular image and deriving at least three
10 statistical functions for the luminosity histogram, the statistical functions include a Weighted Mean (WM) function, a Half Value Position (HVP) function, and a Weighted Standard Deviation (WSD) function; and automatically classifying the image by its statistical functions, which are compared against set parameters for each class of images that are derived from experimental data stored in tables or a database structure. The
15 experimental data can be a collection of human experienced/perceptive data about images from which tables or a knowledge based database is built. The method further includes automatically applying a predetermined set of changes to the image based upon its class.

The system and method in accordance with the present invention further
20 include all interfaces and logics capable of operating in real time and static environments as part of an application or as a stand-alone utility, for example, on a

stand-alone computer, a server-based network, or the Internet, etc. The interfaces provide control of an operator defined quality and compression settings which can be defined on an individual image basis or specified as a rule set for all images processed until such time as another rule set is applied. These settings define the methodology for analysis of the file type to achieve the compression to quality ratio specified. In addition, the system and method are capable of performing pre-image compression enhancement for any known or future compression algorithm, such as JPEG, Wavelet, Fractal, etc. This is also made possible for outputting an enhanced uncompressed image file type, such as BMP or TIFF, etc.

The present invention also addresses the issues of artifacts introduced into images due to the source or previous processing of the image. The artifacts are reduced by applying filters, such as a "Blur" filter that tends to "smear/smudge" the blocking generated as a result of compression or similar to a blocking of dot patterns created by scanned images or GIF. The "Blur" filter reduces the appearance of the blocking throughout the whole picture. The blocking artifacts and the picture details are both blurred. However, the edges that define the original picture content can be restored by applying multiple iterations of the unsharp mask filter in varying amounts (e.g. 15%/15%/15%) whereupon the edges are slowly redefined. Furthermore, the pixel size of the image may determine the amount of unsharp mask applied.

Furthermore, in an automated environment where diverse image sizes and quality need to be enhanced and/or compressed or recompressed, a ratio of file size

in bytes to the total pixel count of an image can be used as a measuring parameter to determine an optimal compression factor so as to retain good visual qualities and achieve a higher degree of compression than that of an original compressed image, e.g. a JPEG. This allows an image processing system to approximate a quality based upon the image's ratio.

In one embodiment, the present invention provides a method of automatically processing a series of input images without operator's intervention. In automatically processing each of the input images, the method includes the steps of providing processing parameters; automatically analyzing, classifying, and enhancing each of the input images without operator's intervention; and outputting at least one enhanced image.

Still in one embodiment, the method outputs more than one enhanced images without re-analyzing, re-classifying, and re-enhancing the input image. The enhanced output images may be in different file types and/or sizes.

Further in one embodiment, the images can be processed in real time on-the-fly or in a batch mode. Further, the images can be processed in a hardware, firmware, or software embodiment that furthermore can be embedded in another system, device, and/or application.

Yet in one embodiment, the method may include one or more of the steps of: pre-processing the input image; automatically resizing the enhanced image; automatically pre-compression enhancing the enhanced image; post-processing the

enhanced image; and automatically compressing the enhanced image.

The present invention also provides a method of automatically processing a series of input images without operator's intervention. In automatically processing each of the input images, the method includes the steps of providing
5 processing parameters; automatically analyzing and classifying the input image without operator's intervention; automatically compressing the image; and outputting at least one compressed image.

Still in one embodiment, the method outputs more than one compressed image without re-analyzing and re-classifying the input image. The compressed output
10 images may be in different file types and/or sizes, and/or of different compression ratios, YUV settings, and Q-factor.

Further in one embodiment, the images can be processed in real time on-the-fly or in a batch mode. Further, the images can be processed in an embedded hardware, firmware, or software that can be embedded in another application.

15 Yet in one embodiment, the method may include one or more of the steps of: pre-processing the input image; resizing the compressed image; pre-compression enhancing the compressed image, post-processing the compressed image; and compressing the compressed image.

The present invention further provides an image processing system of
20 automatically processing a series of input images without operator's intervention. In one embodiment, the system includes an input module for inputting a set of parameters;

and the Halve Value Position range of an image luminosity histogram.

Further in one embodiment, the image enhancement module may include a brightness filter, a contrast filter; a saturation filter; a curve filter; an unsharp mask filter, a blur filter, and/or a hue filter, etc.

5 Yet in one embodiment, the image compression module includes a JPEG compression.

Still in one embodiment, the image resizer resizes the original input image to any smaller size image proportionately to the original image using any specified axis.

10 Further in one embodiment, the image resizer resizes the image to a thumbnail size.

Additionally in one embodiment, the image pre-processor includes a brightness filter, a contrast filter, a saturation filter, and/or an unsharp mask filter.

15 Further in one embodiment, the image post-processor includes a brightness filter, a contrast filter, a saturation filter, and/or an unsharp mask filter.

One aspect of the present invention is that the automatic image processing operations can be manipulated by an operator. For example, an operator can interrupt the automatic image processing operations at any time. The images in the process can be saved in a memory and later restored to continue the operations. For
20 example, if an operator wants to check the quality of the process and/or the quality of a specific image, the images being processed in the operations are saved automatically.

A further aspect of the present invention is that the system and method provide an interactive interface between the system and an operator. For example, the present invention may generate an enhanced image on-the-fly or in real time to allow an operator or user to preview the enhanced image before the system outputs the enhanced
5 image in a given size.

For a better understanding of the invention, reference should be made to the drawings, which form a further part hereof, and to accompanying descriptive matter in which there are illustrated and described specific examples in accordance with the invention.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

Fig. 1 illustrates one embodiment of an image processing system in
5 accordance with the principles of the present invention.

Fig. 2 illustrates one embodiment of an image processing system having additional optional modules in accordance with the principles of the present invention.

Fig. 3 illustrates another embodiment of an image processing system in accordance with the principles of the present invention.

10 Fig. 4 illustrates another embodiment of an image processing system having additional optional modules in accordance with the principles of the present invention.

Figs. 5A-5B illustrate a flow chart diagram of one embodiment of an image processing method in accordance with the principles of the present invention.

15 Figs. 6A-6C illustrate a flow chart diagram of image classification/enhancement operations in one embodiment of an image processing method in accordance with the principles of the present invention.

Figs. 7A-7C are exemplary curves applied to an image in an image enhancement operation in accordance with the principles of the present invention.

20

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the following description of the illustrated embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration several embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized as structural or operational changes and may be made without departing from the spirit and scope of the present invention.

Fig. 1 illustrates one embodiment of an image processing system 100 in accordance with the principles of the present invention. The image processing system 100 includes an image analysis module 102, an image classification module 104, and an image enhancement module 106 wherein each image is automatically analyzed, classified, and enhanced individually based upon each of the characteristics without human intervention when multiple images are submitted for processing. It is noted that the image processing system 100 is capable of processing a single image as well as a series of images.

As shown in Fig. 1, an image or a series of images are input into the image processing system 100. A set of processing parameters are used in the image processing system 100. The processing parameters may include predefined system, device, or operating environment parameters. The predefined system, device, or operating environment parameters may be determined by system resources and transmission bandwidth available or applications that the system is transmitted to or

embedded therein, etc. The processing parameters may also include user input parameters. For example, the processing parameters may include the number of output images, the size of the output image that a user desires, and/or a set of image output quality and compression settings, etc. The settings can be made on an individual image basis or specified in a rule set for all images processed until such time as another rule set is applied. The settings may define the methodology for analysis of a file type to achieve the image compression to quality ratio desired. Further, if a user chooses not to define its own settings, a set of default settings may be used.

The input images may be processed in the image processing system 100 in real time on-the-fly or in a batch mode. The image processing system 100 in accordance with the present invention may also be applied to environments such as web-crawling, a program that searches web pages hosted on the Internet to extract images for purpose of enhancing and further compressing of the images in an automated environment.

Additionally in one embodiment, the image processing system can be embedded in a hardware, firmware, or software which can be embedded in another system or application.

Further, the system 100 may be applied in an automated on-the-fly environment for re-purposing and further compressing of images. The re-purposing and further compressing of image allows for transmission of images to diverse devices having different rendering capacity and image type requirements and further reduction

of the bandwidth required for transmission of the images and the time required to download the images. The process may be applied to fixed wire or wireless transmission of images to devices. One example is that the system applies to images hosted on the Internet where an image content of an HTML page is further compressed and possibly re-purposed as a black and white image to fit the rendering requirements of a device.

Further, the system may be applied in an automated on-the-fly environment where images are sent to an imaging server via the Internet whereupon the images are processed directly upon receipt or from a temporary storage, stored for retrieval, and/or transmitted to the point of origin or some other defined location. In addition, the system may be applied in an automated on-the-fly or static environment where an image of a rendered HTML page is captured, enhanced, compressed, and/or stored and/or transmitted.

In Fig. 1, the image analysis module 102 analyzes a luminosity histogram associated with a particular image and derives the Weighted Mean (WM), Half Value Position (HVP), and Weighted Standard Deviation (WSD) of the image luminosity histogram. The analyzed image is classified by the image classification module 104 and enhanced by the image enhancement module 106 based on the classification.

In Fig. 2, the image processing system 100 may include an image input module 108, a pre-processor 110, a resizer 112, a pre-compression enhancement module

114, a post-processor 116, a compression module 118, and an output module 120. For example, the resizer 112 may resize an enhanced image to a file size defined by a user, for example, to a thumbnail size (e.g. the longest axis of an image having less than 128 pixels). In another example, the image compression module 118 may include a JPEG
5 compression algorithm to compress an image if desired by the user. It is appreciated that these additional modules may be optional, and that the system 100 is not limited to these optional modules.

The pre-processor 110 and the post-processor 116 may include a set of filters, but not limited to, for adjusting the brightness, contrast, and/or saturation, or
10 applying unsharp mask to the image to enhance the image quality of the processed image. It is noted that the terms for brightness, contrast, saturation, and unsharp mask are known in the image processing art.

The input module 108 sets or preserves a white threshold for an input image and determines whether an input image file has a file extension of .jpg, .bmp, or
15 .tif, etc. The input module 108 may also load the input image into a memory in a standard format, for example, a Device Independent Bitmap (DIB) format. The input module 108 determines image attributes, such as file type, file size, file dimension, etc., and obtains an image histogram, such as an image luminosity histogram to calculate the Weighted Mean (WM), Half Value Position (HVP), and Weighted Standard Deviation
20 (WSD) of an image.

The output module 120 may save the output image to a storage medium,

transmit the output image to a local or remote device, or pass the output image to another application, etc. If more than one images are desired to be outputted--for example, a user desires to have a first enhanced image to be of a regular size and a second enhanced image to be of a thumbnail size--, the system 100 automatically
5 generates the second output image based on the user defined file size after generating the first output image. The system 100 does not need to re-load into memory, re-analyze, re-classify, or re-enhance the original input image. The system 100 processes the additional output images based on the user defined parameters for the additional output images for example resizing, pre-compression enhancement, pre- and post-
10 processing, output file type, and compression after the enhancement module 106.

Further, since the image input, the image analysis, image classification, image enhancement, and the image output can be separable, the system 100 is able to automatically process the subsequent input image in the image analysis module 102, image classification module 104, and image enhancement module 106 while outputting
15 previously enhanced images.

In one embodiment of the present invention, the image analysis module 102 analyzes the input image to determine its unique characteristics, for example, color, black/white (B/W), gray scale, luminosity, contrast, brightness, curve, etc. The analyzed data may be stored in tables, a knowledge based database, or the like.

20 In one embodiment of the present invention, the image classification module 104 classifies the input image based upon the Weighted Mean (WM), Half

Value Position (HVP), and Weighted Standard Deviation (WSD) of the image luminosity histogram. The WM, HVP, and WSD are compared to a predetermined set of parameters for each class of images that are derived from experimental data stored in tables, a knowledge based database, or the like. The experimental data can be a collection of human experienced/perceptive data about images from which tables or a knowledge based is built. Then, a predetermined set of changes may be applied to the image based upon its class.

In one embodiment of the present invention, the image enhancement module 106 provides filters and masks to change the characteristics of the input image such that the image is improved and enhanced for its visual qualities.

In one embodiment of the present invention, the image processing system 100 provides a user interface which allows a user to define an end-product image characteristics, for example, the highest compression, the best compression to quality ratio, a specific or near loss-less image characteristic, etc.

Fig. 3 illustrates another embodiment of the image processing system 122 in accordance with the principles of the present invention. The system 122 includes the analysis module 102, the classification module 104, and a compression module 124. The image is compressed by the compression module 124.

In Fig. 4, the system 122 may further include the image input module 108, the pre-processor 110, the resizer 112, the pre-compression enhancement module 114, the post-processor 116, the compression module 118, and the output module 120.

It is appreciated that these additional modules may be optional, and that the system 122 is not limited to these optional modules.

Figs. 5A-5B illustrate a flow chart diagram of one embodiment of an image processing method in accordance with the principles of the present invention.

5 As shown in Fig. 5A, an image processing operation flow 126 starts with an operation of setting a preserve white threshold for an input image in an operation 128. In one embodiment, the preserve white threshold may be set to 253-255 out of a gray scale of 0-255. Accordingly, for the portions which have the gray scale of 253 or more, the white is preserved in the subsequent image processing. It is appreciated that a
10 border can be adjusted and/or preserved with a certain gray scale within the scope of the present invention. Then, the operation flow 126 determines whether the input image is a compressed image, such as a JPEG image or an uncompressed image, such as a BMP or TIFF, in an operation 130. In one implementation shown in Fig. 5A, if the input image is not a JPEG, BMP, or TIFF file, the operation flow 126 may be terminated. It
15 is appreciated that the implementation can be varied such that other types of compressed or uncompressed images can be processed without departing from the scope of the present invention.

In Fig. 5A, if the input image is a JPEG, BMP, or TIFF, the image is loaded into a memory or buffer in a standard format, such as a DIB format, in an
20 operation 132. Then, the image attributes, such as file type, file size, and file dimension, are determined in an operation 134 by determining the characteristics of a

physical file. It is appreciated that the file type, file size, and file dimension determination is known in the art and not the focus of the present invention. Next, an image luminosity histogram of the input image is generated in an operation 136. The image luminosity histogram may include Weighted Mean (WM), Weighted Standard Deviation (WSD), and Half Value Position (HVP). The details of the WM, WSD, and HVP are described later in details. It is appreciated that the other types of image histograms can be used without departing from the scope of the present invention.

Still in Fig. 5A, the operation flow 126 determines whether a user desires to pre-process the input image in an operation 138. If "Yes", the brightness, contrast, and saturation percentage of the image may be adjusted based on the user definition in operations 140, 142, and 144, respectively. Further, an unsharp mask may be applied to the image, for example applying a mask percentage of a radius equal to 1 and a threshold equal to 1 in an operation 146. The pre-processing mask percentage can also be defined by the user. It is appreciated that the sequence or order of the operations 140-146 can be varied within the scope of the present invention.

If the image pre-processing is not desired in the operation 138, i.e. "No", the image is analyzed/classified based on the image histogram statistics in an operation 148. The detailed analysis/classification is described later in Figs. 6A-6C.

Then, the operation flow 126 determines whether an image enhancement is desired in an operation 150. If "Yes", a curve is applied based on analysis of the image histogram statistics in an operation 152. Further, the percentage of brightness,

contrast, and saturation of the image is adjusted based on the analysis of the image histogram statistics in operations 154, 156, and 158, respectively. It is appreciated that the sequence or order of the operations 152-158 can be varied within the scope of the present invention. Then, the operation flow 126 goes to Fig. 5B. On the other hand, if the image enhancement is not desired in the operation 150, i.e. "No", then the operations 152-158 are bypassed, and the operation flow 126 goes to Fig. 5B directly.

In Fig. 5B, the operation flow 126 determines whether the user desires to resize the image in an operation 160. If "Yes", the image is resized along its X axis, Y axis, or the longest axis in an operation 162. Then, the operation flow 126 determines whether the resized image is a thumbnail size image (e.g. the longest axis of the image having less than 128 pixels) in an operation 164. If the resized image is a thumbnail image, i.e. "Yes", the brightness of the image is adjusted by a predefined percentage, such as 2%, etc. in an operation 166, and an unsharp mask is applied by a predetermined percentage having a predetermined radius and/or threshold, for example, by 10% having a radius of 1 and threshold of 0 in an operation 168.

If the resized image is not a thumbnail size image in the operation 164, i.e. "No", or if the image is not desired to be resized in the operation 160, i.e. "No", then the operation flow 126 determines whether an unsharp mask should be applied based on analysis of the image histogram statistics in an operation 170. If an unsharp mask should be applied, i.e. "Yes", the operation flow 126 determines whether the input image is an uncompressed image, such as a BMP or TIFF image, or the input image is a

009077-11120260

compressed image, such as a JPEG image in operations 172, 174. If the input image is a BMP or TIFF image, then the operation flow 126 determines whether the largest dimension of the input image is between a range, for example, between but not including 128 and 450 pixels in an operation 176. If the largest dimension of the input image is within 128-450 pixel range, i.e. "Yes", an unsharp mask is applied by a predetermined percentage in an operation 178, for example, by 30%, which has a radius and threshold based on the image analysis. Next, the operation flow 126 goes to determine whether an image post-processing is desired in an operation 182.

If the largest dimension of the input image is not within 128-450 pixel range in the operation 176, i.e. "No", or if the input image is a JPEG, BMP, or TIFF image from the operations 172 and 174, then an unsharp mask is applied in an operation 180 by a percentage, radius, and threshold based on the image analysis. Next, the operation flow 126 goes to determine whether an image post-processing is desired in an operation 182.

If the user desires to post-process the image in the operation 182, i.e. "Yes", the brightness, contrast, and saturation percentage of the image may be adjusted by the user's definition in operations 184, 186, and 188, respectively. Further, an unsharp mask may be applied to the image by post-processing mask percentage, for example, having a radius equal to 1 and a threshold equal to 1 in an operation 190. The post-processing mask percentage can also be defined by the user. It is appreciated that the sequence or order of the operations 184-190 can be varied within the scope of the

present invention.

If the post-processing is not desired in the operation 182, i.e. "No", then the operation flow 126 may determine whether a trial image or a preview of an output image is desired in an operation 192. If a trial image is desired, i.e. "Yes", then a logo, such as a company's logo, e.g. VisualGold™ logo, may be embossed in the trial image in an operation 194. Next, the operation flow 126 goes to determine whether an image output is a JPEG image in an operation 196.

If the trial image is not desired in the operation 194, then the operation flow 126 goes to determine whether an image output is a JPEG image in the operation 196. Also, since each of the processing steps is separable from each other, the operation flow 126 can be interrupted at any time. Once interrupted, the image at the time of interruption is automatically saved for review and further processing.

If the image output is a JPEG image in the operation 196, i.e. "Yes", then the YUV color settings and Q-factor for the JPEG image are set in an operation 198.

The YUV color settings and Q-factor are described later in details. Next, the image output is saved to a storage medium, transmitted to a device, or passed to an application, etc., in an operation 200. If the image output is not a JPEG image in the operation 196, then the operation 198 is bypassed, and the operation flow 126 goes to an operation 200 to save the image output to a storage medium, or to transmit the image output to a device, or to pass the image output to another application, etc.

When a compression is desired to drive an output file to a specific file

size, the operation flow 126 further includes an operation 201 to determine YUV settings and Q-factor.

Then, the operation flow 126 goes to determine whether additional image outputs of the same input image are desired in an operation 202. If additional image outputs are not desired, the image processing operation flow 126 is terminated. If additional image outputs are desired, the image processing operation flow 126 goes back to the operation 160 to determine whether the additional image needs to be resized and continues the steps as described above. It is noted that the additional output images are generated without re-analyzing, re-classifying, or re-enhancing/re-compressing the input image.

It is appreciated that additional operations can be implemented within the scope of the present invention. For example, the operation flow 126 may include operations such that the processed image can be sampled and compared to the input image to allow a user to adjust the processing parameters to achieve the desired output images. Accordingly, the image processing method may include steps of establishing the need for further processing, and providing successive filter settings for each consecutive filter pass by a measurable parameter or a change between input image and processed image, and its approximation to a default or user defined parameter. It is noted that a database containing all process information unique to the image characteristics upon which the process draws information for further processing can be provided. Further, it is noted that an archive of pre-processing and post-processing

settings for all images previously processed can be provided. All images previously are processed for a given set of user defined characteristics upon which the process draws information for all future image processing to reduce process iterations for desired results.

5 Exemplary image analysis, classification, and enhancement/compression processes are described herewith in details. Generally, there are three main steps. The first step is to analyze an image's histogram, e.g. luminosity histogram, to derive the three statistical functions, the Weighted Mean, the Half Value Position, and the Weighted Standard Deviation. The second step is to classify the image by its statistical
10 functions which are compared against set parameters for each class of images. The classes of images are derived from experimental data. The experimental data can be a collection of human experienced/perceptive data about images from which tables and a database is built. The third step is to apply a set of predetermined changes to the image based upon its class. The changes for each class vary but generally include brightness,
15 contrast, saturation, curve, and unsharp mask. It is appreciated that the changes may be applied in a specific degree and order, and that the application of the changes may also take into account for the compression that may be applied after this process and/or other processes such as resizing of an image.

I. Analysis of An Input Image

20 In general, an input image is converted to a standard format, for example, a DIB format, to improve visual qualities of the input image. Each image is then

analyzed for its unique luminosity and color characteristics/attributes, classified, and enhanced to improve its visual qualities. The method includes all interfaces and logic to operate in a dynamic environment or a static environment as part of an application or as a stand-alone utility. The input image can be a pre-compressed image via a
5 compression algorithm, such as JPEG, Wavelet, and Fractal, etc. The input image can also be an uncompressed image, such as a BMP or TIFF image.

Analysis of both statistical and visual qualities of the images may produce the following results. For example, images can be divided into classes based upon distinctions in images' luminosity histogram: a) the Weighted Mean (WM); b) the
10 Weighted Standard Deviation (WSD); and c) the direction and amount of separation between the Weighted Mean and the Half Value Position (HVP), etc.

By analyzing each component, the following results may occur: a) the higher the Weighted Mean, the lighter the image color; it is noted that this may be the main determining criteria for image classification; b) the higher the Standard Deviation,
15 the higher the contrast of the image; c) depending on the Weighted Mean and Standard Deviation, the difference between the Weighted Mean and the Half Value Position determines the exposure of an image. For example, an image with a higher Standard Deviation, a greater difference in Half Value Position, and a lesser Weighted Mean, results in an over-exposed image. While images that possess these values within a
20 certain constraint are considered as images of "normal" exposure. This generally forms

the basis for the analysis, classification, and identification of the required enhancements to be performed on the image.

The analysis of the image histogram is derived from the three statistical functions as defined below:

5

1) Weighted Mean:
$$\frac{\sum_{i=0}^{255} a_i p_i}{\sum_{j=0}^{255} a_j}$$

2) Weighted Standard Deviation:
$$\sqrt{\sum_{i=0}^{255} \left(\frac{a_i}{\sum_{j=0}^{255} a_j} \left(p_i - \frac{\sum_{k=0}^{255} a_k p_k}{\sum_{l=0}^{255} a_l} \right)^2 \right)}$$

10 Where p_n is defined as the position or ordinal values of the histogram, and a_n is defined as the amplitude of the pixels at each n^{th} ordinal.

3) Half Value Position: This is defined as the ordinal in the Histogram where all the pixels below that ordinal, sum (left to right) to at least half the pixels of the image.

15 It is appreciated that the definitions of the above three functions may be varied within the scope of the present invention.

II. Classification and Enhancement Application Based on Classification

The results of the analysis of the image histogram are used to classify and enhance the image.

TABLE 1 below defines a rule set for classifying an image and an enhancement rule set for each classification of images. It is appreciated that TABLE 1 is an exemplary illustration of qualitative analysis and can be varied within the scope of the present invention. Therefore, TABLE 1 is considered as one embodiment of the present invention, and the invention is not limited thereby.

10

KEYS FOR TABLE 1	
WM= Weighted Mean	B = Brightness
HV = Half Value Position	C = Contrast
WSD= Weighted Standard Deviation	Sat = Saturation
CRV = curves	Mask = BMP/TIFF Unsharp Mask

TABLE 1

Operation Identification Shown in Figs. 6A-6C	Classification Rules	Enhancement Rules*
A	WM<30	Mask
D1	30≤WM<100 WSD<40 WM-HV <15	2B, 4C, 2Sat 20% Mask
D2	30≤WM<60 WSD<40 WM-HV >15	CRV1 -2B, 2Sat 20% Mask

Operation Identification Shown in Figs. 6A-6C	Classification Rules	Enhancement Rules*
D3	$60 \leq WM < 90$ $WSD < 40$ $ WM-HV > 15$	2B, 4C, 2Sat 20% Mask
D	$90 \leq WM < 100$ $WSD < 40$ $ WM-HV > 15$	CRV1 -2B, 2Sat 20% Mask
C2	$30 \leq WM < 50$ $WSD > 60$	CRV2 30% Mask
C1	$50 \leq WM < 80$ $WSD > 60$	CRV3 -5B, -3C, 5Sat 30% Mask
C	$80 * WM < 100$ $WSD > 60$	3B, -2C, 3Sat 30% Mask
E	$30 \leq WM < 60$ $40 \leq WSD \leq 60$ $ WM-HV < 10$	3B, 4C, 7Sat 30% Mask
G	$60 \leq WM < 80$ $40 \leq WSD \leq 60$ $ WM-HV < 10$	CRV4 3B, 4C, 2Sat 30% Mask
J	$80 \leq WM < 100$ $40 \leq WSD \leq 60$ $ WM-HV \leq 10$	CRV5 2C, 4Sat 30% Mask
F	$30 \leq WM < 60$ $40 \leq WSD \leq 60$ $WM-HV > 10$	CRV6 4B, 2C 30% Mask
H	$60 \leq WM < 80$ $40 \leq WSD \leq 60$ $WM-HV > 10$	CRV7 -2B, 5Sat 30% Mask
K	$80 \leq WM < 100$ $40 \leq WSD \leq 60$ $WM-HV > 10$	CRV8 -2B, 2C 30% Mask
I	$60 \leq WM < 80$ $40 \leq WSD \leq 60$ $HV-WM > 10$	CRV7 6B, 5Sat 30% Mask

Operation Identification Shown in Figs. 6A-6C	Classification Rules	Enhancement Rules*
L	$80 \leq WM < 100$ $40 \leq WSD \leq 60$ $HV-WM > 10$	CRV7 6B, 2C, 5Sat 30% Mask
A4	$WM > 220$	30% Mask
A1	$200 < WM \leq 220$ $WSD > 60$	30% Mask
A2	$200 < WM \leq 220$ $WSD < 40$	3C, 10Sat 20% Mask
A3	$200 < WM \leq 220$ $40 \leq WSD \leq 60$	CRV8 30% Mask
X	$150 < WM \leq 175$ $WSD > 60$ $ WM-HV \leq 15$	1B, -3C, 3Sat 30% Mask
X1	$175 < WM \leq 200$ $WSD > 60$ $ WM-HV \leq 15$	CRV9 2C, 3Sat 30% Mask
W	$150 < WM \leq 175$ $WSD > 60$ $ WM-HV > 15$	CRV10 3B, 2C, 6Sat 30% Mask
W1	$175 < WM \leq 200$ $WSD > 60$ $ WM-HV > 15$	CRV10 4B, 4Sat 30% Mask
Y	$150 < WM \leq 200$ $WSD < 40$	-1B, 4C 30% Mask
Z2	$150 < WM \leq 200$ $40 \leq WSD \leq 60$ $ WM-HV > 15$	CRV11 2C, 5Sat 30% Mask
Z	$150 < WM \leq 175$ $40 \leq WSD \leq 60$ $ WM-HV < 15$	2C, 4Sat 22% Mask
Z1	$175 < WM \leq 200$ $40 \leq WSD \leq 60$ $ WM-HV < 15$	-2B, 3Sat 30% Mask

Operation Identification Shown in Figs. 6A-6C	Classification Rules	Enhancement Rules*
M	$100 \leq WM \leq 120$ $45 \leq WSD \leq 55$ 30% Mask	CRV12 2B, 5Sat 30% Mask
N	$120 < WM \leq 130$ $45 \leq WSD \leq 55$	CRV12 1B, 3Sat 30% Mask
O	$130 < WM \leq 150$ $45 \leq WSD \leq 55$	30% Mask
P	$100 \leq WM \leq 150$ WSD < 40	CRV13 -4B, -3Sat 20% Mask
Q	$100 \leq WM \leq 150$ $40 \leq WSD < 45$	3C, 3Sat 20% Mask
R1	$100 < WM \leq 130$ $55 < WSD \leq 60$	30% Mask
R	$130 < WM \leq 150$ $55 < WSD \leq 60$	CRV12 3Sat 30% Mask
V1	$100 \leq WM < 130$ WSD > 70 $ WM - HV < 8$	CRV14 -1B, 4Sat 30% Mask
V	$130 \leq WM < 150$ WSD > 70 $ WM - HV < 8$	CRV15 -3C, 7Sat 30% Mask
S1	$100 \leq WM < 130$ WSD > 60 $ WM - HV < 15$	CRV16 -2B, 1C, 2Sat 30% Mask
S	$130 \leq WM \leq 150$ WSD > 60 $ WM - HV < 15$	CRV17 1B, -3Sat 30% Mask
T	$100 \leq WM \leq 130$ WSD > 60 WM-HV > 15	CRV18 1C, 6Sat 30% Mask
T1	$130 \leq WM \leq 150$ WSD > 60 HV-WM > 15	CRV19 -1B, 2Sat 30% Mask

Operation Identification Shown in Figs. 6A-6C	Classification Rules	Enhancement Rules*
U	100≤WM<130 WSD>60 HV-WM>15	CRV20 -4B, 5Sat 30% Mask
U1	130≤WM≤150 WSD>60 WM-HV>15	CRV21 -2B, 2Sat 30% Mask

Figs. 6A-6C illustrate a flow diagram of image classification/
enhancement operations in one embodiment of an image processing method in
accordance with the principles of the present invention. The image enhancement
5 operations or rules shown in Figs. 6A-6C correspond to TABLE 1. For example, an
image having the statistics in TABLE 1A below would apply image enhancement rule
"G" in Fig. 6A, following operational blocks 204-222. The order in which the
enhancement functions are specified in the rule set is one implementation of present
invention. It is appreciated that the other orders can be used without departing from the
10 present invention.

TABLE 1A

Weighted Mean	Weighted Standard Deviation	Half Value Position
66.3	45.9	72

It is appreciated that other classification/enhancement rules can be used
without departing from the scope of the invention. It is also appreciated that the above

classification/enhancement rules may be implemented in an algorithm format within the scope of the invention.

It is appreciated that the other image processing operations such as sharpening, masking, etc., can be used within the scope of the present invention. It is
5 also appreciated that the degree of adjustment in brightness, contrast, saturation, or the percentage or amount of curve, unsharp mask, etc., can be varied without departing from the scope of the present invention.

Exemplary image processing filters or tools that can be used in the present invention are Brightness, Contrast, Saturation, Curves, Unsharp Mark, Preserve
10 White, Resizing, etc.

It is appreciated that the image processing filters are not limited to the above, and that the other filters can be used, such as color balance, tone balance, and/or hue, cropping, etc.

Figs. 7A-7C illustrate exemplary curves. As described above, curves
15 allow enhancement of luminosity characteristics in a given area of an image when determined by the classification process. The curves enhancement function is defined as a re-mapping of luminosity or density values versus exposure. The benefit of this function occurs when an image needs a shift in luminosity for specific portions in the image. For example, images with shadows are able to shift those shadows to a higher
20 luminosity while the entire image is not shifted or made lighter. The way of achieving this technique involves a mapping of luminosity values which are valued from 0-255 to

new luminosity values in that range. The curve applied to an image is determined by the classification of the image. Three exemplary curves applied to map the luminosity values of an input image are shown in Figs. 7A-7C, respectively. In Figs. 7A-7C, the line starts in the lower left, i.e. at black color (luminosity level of 0) and goes to the upper right, i.e. at white color (luminosity level of 255). In Fig. 7A, a curve demonstrates no alteration or mapping to an image. For example, an input luminosity level of 143 remains at 143. In Fig. 7B, a curve is applied to brighten the entire image. For example, an input luminosity level of 143 is brightened to luminosity level of 184. In Fig. 7C, a curve is applied to darken the over-all image. For example, an input luminosity level of 143 is darkened to luminosity level of 109. It is noted that in Figs. 7B and 7C, an entire image is brightened or darkened. It is appreciated that a curve can be applied to brighten or darken a certain portion of the image. It is also appreciated that other curves can be used within the scope of the invention.

To further illustrate a curve in a table format, TABLE 2 provides one exemplary curve for luminosity mapping.

TABLE 2: Curves Table Example

Curves Table Example								
255	254	253	252	251	250	249	248	247
255	253	251	249	248	246	244	242	241
246	245	244	243	242	241	240	239	238
239	237	235	234	232	231	229	228	226
237	236	235	234	233	232	231	230	229
225	223	222	221	220	219	218	217	216

Curves Table Example								
228	227	226	225	224	223	222	221	220
215	214	213	212	211	210	209	208	207
219	218	217	216	215	214	213	212	211
207	206	205	205	204	203	203	202	201
210	209	208	207	206	205	204	203	202
201	200	200	199	199	198	198	197	197
201	200	199	198	197	196	195	194	193
196	196	195	195	194	194	193	193	192
192	191	190	189	188	187	186	185	184
192	191	190	189	189	188	187	186	186
183	182	181	180	179	178	177	176	175
185	184	183	183	182	181	180	180	179
174	173	172	171	170	169	168	167	166
178	177	176	175	174	173	172	171	170
165	164	163	162	161	160	159	158	157
169	168	167	166	165	164	163	162	162
156	155	154	153	152	151	150	149	148
160	159	158	157	156	155	154	153	152
147	146	145	144	143	142	141	140	139
151	149	148	147	146	145	144	143	142
138	137	136	135	134	133	132	131	130
141	140	138	137	136	135	134	133	132
129	128	127	126	125	124	123	122	121
131	130	129	127	126	125	124	123	122
120	119	118	117	116	115	114	113	112
121	120	119	117	116	115	114	113	112

Curves Table Example								
111	110	109	108	107	106	105	104	103
111	110	109	107	106	105	104	103	102
102	101	100	99	98	97	96	95	94
101	100	99	98	97	96	95	94	93
93	92	91	90	89	88	87	86	85
92	91	90	89	88	87	86	85	84
84	83	82	81	80	79	78	77	76
83	82	81	80	79	78	77	76	75
75	74	73	72	71	70	69	68	67
74	73	72	71	71	70	69	68	68
66	65	64	63	62	61	60	59	58
67	66	65	65	64	63	62	62	61
57	56	55	54	53	52	51	50	49
60	59	59	58	57	56	56	55	54
48	47	46	45	44	43	42	41	40
53	53	52	51	50	50	49	48	47
39	38	37	36	35	34	33	32	31
46	46	45	44	43	42	42	41	40
30	29	28	27	26	25	24	23	22
39	38	37	36	35	34	33	33	31
21	20	19	18	17	16	15	14	13
30	28	27	25	24	23	21	20	18
12	11	10	9	8	7	6	5	4
17	16	14	13	11	10	8	7	5
3	2	1	0					
4	2	1	0					

Further, an unsharp mask enhances an image by making it sharper without accentuating small imperfections in an image. Thus, an image gains more details and clarity while preserving visual continuity. The unsharp mask percentage applied to an image is dependent upon an input image file type and is handled differently for a compressed image, such as a JPEG image, from an uncompressed image, such as a BMP or TIFF image.

Pre-compression Enhancement Process for Images that are Resized

The image processing system in accordance with the present invention addresses issues of image quality degradation resulting from either resizing of an image or artifacts introduced in the process of compressing a previously compressed image, or a combination of both processes.

Post Resizing Enhancement Process

High quality digital source images, such as BMP and TIFF files that have not been previously compressed, may need to be resized. If the image is resized by dividing the pixel dimensions by some number that, when divided into the number of pixels leaves no fraction, then the sharpness of the image is not significantly degraded in the process. For example, reducing 400 pixels to 200 pixels or 900 pixels to 300 pixels would not greatly alter the apparent sharpness of the image. If the image is resized by another factor such as 400 pixels to 299 pixels, significant interpolation of the image occurs resulting in the loss of image sharpness or clarity. The loss of sharpness generated from this interpolation process can be significantly regained by

increasing the edge definition of the image content through application of an unsharp mask filter. The percentage strength of the mask can be altered to optimize the amount of edge enhancement applied based on the ratio of reduction from the original image, the absolute physical dimensions of the reduced image, the amount of interpolation required to achieve the desired resized dimensions, the type of interpolation algorithm used, or a combination of all of the above factors.

TABLE 3 below defines an exemplary unsharp mask applied to a resized image, which is not previously compressed, based on the image's longest axis dimension.

TABLE 3 (BMP & TIFF unsharp mask)

MASK TABLE FOR BMP & TIFF IMAGES

DPI	Mask % to be applied
0 to 128	30
128 to 450	35
450+	30

The enhancement process also considers the special case of thumbnails, e.g. images of approximately 128 pixels or less on the longest axis, wherein the information defining the image is significantly reduced. Image sharpness of thumbnail-sized images is greatly improved by applying an additional percentage of unsharp mask, and a small increase in contrast, brightness, and, for color images, saturation. These

filters allow the image to retain high visual qualities while attaining higher degrees of compression than when not applying such filters.

It is appreciated that the enhancement process is not limited to the special case of thumbnails, and that the enhancement process can be used in other resizing applications within the scope of the present invention.

Enhancement Process for Resizing Previously Compressed Images

The rules that govern usage of an unsharp mask applied to an input image previously compressed, such as a JPEG image, require different unsharp mask optimization rules from those applied to images that have not been previously compressed.

The percent of unsharp mask to be applied in the resizing of a previously compressed JPEG image requires compensating for the variables described as optimal for uncompressed images and, in most cases, the percentage of the unsharp mask is then reduced from that uncompressed optimal setting so as not to accentuate the artifacts introduced in the initial compression process.

Determining the factor to reduce the amount of mask for a given JPEG file can be calculated in several ways. In one method, the ratio of total pixel count of the DIB (Device Independent Bitmap) is compared with the original compressed JPEG image file size in kilobytes. This ratio is used as criteria for exemplary TABLE 4 below to obtain the appropriate unsharp mask percentage to be applied to the image.

TABLE 4

MASK TABLE FOR JPEG IMAGES

Ratio is the total pixels of an image divided by the file
size (K)

Ratio	Mask % to be applied
0-1500	42
1501-1900	36
1901-2300	26
2301-2600	23
2601-3500	20
3501-4500	17
4501-6000	15
6001-9000	10
9001-12000	7
12001+	5

The application of the use of an unsharp mask in this fashion enhances edge definition and, therefore, apparent sharpness to the image without adding significantly to the picture's high frequency content. Since high frequency limits how effectively a compression algorithm can be in reducing file size, images processed in this manner can be compressed further, with less visible artifacts, high apparent image sharpness, and greatly reduced file size.

The pre-compression, post resizing enhancement is applied automatically without operator's intervention. The algorithm can also be applied in a networked or server-based environment where no human intervention is possible.

5 Enhancement Process for Reducing Apparent Artifacts in Images

 An image may have had artifacts introduced into the picture or image through a scanning process, compression algorithm, color reduction such as experienced in a GIF image for the Internet or by scanning a printed page including half-tone dot patterns. The present invention reduces these visible artifacts and allows for the
10 creation of a second-generation image that can be resized and compressed with improved edge definition and reduced artifacts as compared with the source image.

 The process utilizes a “Blur” filter that tends to “smear/smudge” the blocking generated as a result of the compression or similar to a blocking of dot patterns created by scanned images or GIF. Because the “Blur” filter reduces the appearance of
15 the blocking throughout the whole picture, edge definition of the image degrades and thus must be restored. The application of unsharp mask filter is then applied in multiple iterations in same or varying amounts (e.g. 15%/15%/15%) whereupon the image’s intended edges are redefined with the artifacts remaining less evident.

 It is appreciated that other filters may be applied to pre-compression,
20 post-resizing enhancing of images without departing from the scope of the present invention. It is further appreciated that the degree of application of the filters applied,

e.g. "Blur", "unsharp mask", etc., can be varied without departing from the scope of the present invention.

III. Compression of the Output Image

The image processing system may include a user interface that allows a user to compress an enhanced image. As an example, an enhanced JPEG image can be further compressed by setting YUV settings and Q-factor, as well as a unique file name for each output image when applied to a batch of images.

It is appreciated to those skilled in the art that the Q-Factor relates to a term that represents the quality versus compression ratio used in saving an image as a JPEG file. It is also appreciated to those skilled in the art that a YUV Color Difference Coordinate System relates to a color coordinate system that represents RGB colors in terms of the luminosity Y and two difference colors. The Y tristimulus value represents luminosity, while the U and V variables represent a percentage of luminosity less Blue and Red, respectively. It is appreciated that the compression applied is not limited to the compressed JPEG image, without departing from the scope of the present invention.

IV. Compression of an Image to a Target File Size

The image processing system includes a user interface that allows a user to drive an input image to an approximate file size. In one embodiment of the present invention, this may be accomplished with a series of tables. This feature involves saving an input image in a memory or buffer as a 30 Q-factor/4:4:4 YUV setting. The

file size (in kilobytes) is then compared against a file size, such as a BMP file size, of an input image to obtain a percentage. This percentage is referenced and used to map to the correct table. An example of these tables is given in a JPEG Compression Approximation in TABLE 5. Of course, those skilled in the art appreciate that many examples of such tables may be provided, and that TABLE 5 is but one of such examples. Accordingly, the invention is not limited to such examples as others may be provided without departing from the scope and spirit of the invention.

TABLE 5

YUV Setting	QFactor 2	QFactor 5	QFactor 10	QFactor 15	QFactor 20	QFactor 25	QFactor 30	QFactor 35	QFactor 40
411	2.47	1.98	1.65	1.36	1.2	1.07	1	0	0.856
422	2.695	2.075	1.675	1.38	1.21	1.075	1	0.925	0.867
444	2.92	2.17	1.7	1.4	1.22	1.08	1	0.93	0.878

An exemplary process of compressing an image on a single image input basis is as follows:

1. Saving the image (enhanced or not) as a 30 Q factor JPEG, 444 JPEG to a memory or buffer, recording the file size of this image, and using it as a reference.
2. Multiplying this file size by the factors dependent upon the YUV setting chosen by the user.

3. Depending upon the file size chosen, the appropriate Q-Factor is applied to the image in order to output the image as a JPEG image.

Accordingly, the user interface allows for various compression and/or
5 quality change settings. Any known compression algorithm, such as the JPEG compression algorithm, can be used within the scope of the invention. In one embodiment, the first user option is a series of compression choices that involve either a slider bar or a set of numerical options. The user interface allows for image compression ranging from, for example, 20 to 60 in Q-Factor while utilizing a 4:1:1
10 YUV setting.

The image compression range, for example, from 20 to 60 in Q-Factor while utilizing a 4:1:1 YUV setting, is imposed to limit the degradation of images that normally occurs beyond a 60 Q-Factor. For example, a 4:1:1 YUV setting causes a need for an additional +5 saturation to compensate for the color change in an image.
15 The user interface also allows for a separate quality choice. This gives the user the option to compress an image while still being assured a high quality image. In another example, the Q-Factor ranges from 2 to 30 and involves a YUV setting of 4:4:4, which may not require any additional saturation.

The above specification, examples and data provide a complete and
20 enabling description of the invention. Since many embodiments of the invention can be

made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

CLAIMS

What is claimed is:

1. A method of automatically processing a series of input images without operator's intervention, in automatically processing each of the input images, the method
5 comprising:
 providing processing parameters;
 automatically analyzing, classifying, and enhancing the input image without operator's intervention; and
 outputting at least one enhanced image.
10
2. The method of claim 1, further comprising outputting a plurality of enhanced images with different file types without re-analyzing, re-classifying, and re-enhancing the input image.
- 15 3. The method of claim 1, further comprising outputting a plurality of enhanced images with different file sizes without re-analyzing, re-classifying, and re-enhancing the input image.
4. The method of claim 1, wherein the input images are processed in real time on-
20 the-fly.

5. The method of claim 1, wherein the input images are processed in a batch mode.

6. The method of claim 1, wherein the input images are processed in an embedded software.

5

7. The method of claim 1, wherein the input images are processed in an embedded hardware.

8. The method of claim 1, wherein the input images are processed in an embedded
10 firmware.

9. The method of claim 1, wherein the step of automatically analyzing, classifying,
and enhancing the input image includes applying an individual image enhancement
independently to each of the input images.

15

10. The method of claim 1, further comprising pre-processing the input image
before analyzing, classifying, and enhancing the input image.

11. The method of claim 1, further comprising resizing the enhanced image.

20

12. The method of claim 1, further comprising compressing the enhanced image.

13. The method of claim 11, further comprising compressing the enhanced image before outputting the resized image.

5 14. The method of claim 13, further comprising automatically applying at least one filter in a pre-compression, post-resizing enhancement.

15. The method of claim 13, further comprising post-processing the enhanced image before compressing the enhanced image.

10

16. The method of claim 1, wherein the processing parameters define the number of the output images.

17. The method of claim 11, wherein the processing parameters define resizing
15 parameters.

18. The method of claim 12, wherein the processing parameters define compression parameters.

20 19. The method of claim 13, wherein the processing parameters define compression parameters.

20. The method of claim 1, further comprising viewing the enhanced image before outputting.

5 21. The method of claim 1, wherein the input images are processed in a server computer of a network system, an output destination for the output image is coupled to the network system.

22. The method of claim 21, wherein the network system is Internet, whereby the
10 system is capable of being applied in an automated on-the-fly environment where images are sent to the server computer via the Internet whereupon the images are processed and transmitted to the output destination.

23. A method of automatically processing a series of input images without operator's
15 intervention, in automatically processing each of the input images, the method comprising:

providing processing parameters;

automatically analyzing and classifying each of the input images without
operator's intervention;

20 automatically compressing the image; and
outputting at least one compressed image.

24. The method of claim 23, further comprising outputting a plurality of compressed images with different file types without re-analyzing and re-classifying each of the images.

5

25. The method of claim 23, further comprising outputting a plurality of compressed images with different file sizes without re-analyzing and re-classifying the input image.

26. The method of claim 23, wherein the input images are processed in real time on-the-fly.

10

27. The method of claim 23, wherein the input images are processed in a batch mode.

28. The method of claim 23, wherein the input images are processed in an embedded software.

15

29. The method of claim 23, wherein the input images are processed in an embedded hardware.

20

30. The method of claim 23, wherein the input images are processed in an embedded

firmware.

31. The method of claim 23, wherein the step of automatically analyzing,
classifying, and enhancing the input image includes applying an individual image
5 enhancement independently to each of the input images.

32. The method of claim 23, further comprising pre-processing the input image.

33. The method of claim 23, further comprising resizing the classified image before
10 compressing the image.

34. The method of claim 33, further comprising automatically applying at least one
filter in a pre-compression, post-resizing enhancement.

15 35. The method of claim 34, further comprising post-processing the resized image
before compressing the image.

36. The method of claim 23, wherein the processing parameters define the number
of the output images.

20

37. The method of claim 33, wherein the processing parameters define resizing

parameters.

38. The method of claim 23, wherein the processing parameters define compression parameters.

5

39. The method of claim 23, further comprising viewing the compressed image before outputting.

40. The method of claim 23, wherein the input images are processed in a server
10 computer of a network system, an output destination for the output image is coupled to the network system.

41. The method of claim 40, wherein the network system is Internet, whereby the
system is capable of being applied in an automated on-the-fly environment where
15 images are sent to the server computer via the Internet whereupon the images are processed and transmitted to the output destination.

42. An image processing system for automatically processing a series of input
images without operator's intervention, comprising:
20 an image analysis module for automatically analyzing each of the input images;
an image classification module for automatically classifying the analyzed image;

an image enhancement module for automatically enhancing the classified image based on classification; and

an output module for outputting at least one enhanced image.

5 43. The system of claim 42, wherein the output module outputs a plurality of enhanced images with different file types without re-analyzing, re-classifying, and re-enhancing the input image.

10 44. The system of claim 42, wherein the output module outputs a plurality of enhanced images with different file sizes without re-analyzing, re-classifying, and re-enhancing the input image.

15 45. The system of claim 42, wherein the image analysis module, the image classification module, the image enhancement module, and the output module process the input image in real time on-the-fly.

20 46. The system of claim 42, wherein the image analysis module, the image classification module, the image enhancement module, and the output module process the input image in a batch mode.

47. The system of claim 42, wherein the image analysis module, the image

classification module, the image enhancement module, and the output module process the input image in an embedded software.

48. The system of claim 42, wherein the image analysis module, the image
5 classification module, the image enhancement module, and the output module process the input image in an embedded hardware.

49. The system of claim 42, wherein the image analysis module, the image
classification module, the image enhancement module, and the output module process
10 the input image in an embedded firmware.

50. The system of claim 42, wherein the image enhancement module applies an individual image enhancement independently to each of the input images.

15 51. The system of claim 42, further comprising a pre-processor for pre-processing the image before analyzing, classifying, and enhancing the input image.

52. The system of claim 42, further comprising an image resizer for resizing the enhanced image.

20

53. The system of claim 42, further comprising an image compression module for

compressing the enhanced image before outputting the enhanced image.

54. The system of claim 52, further comprising an image compression module for
5 compressing the enhanced image before outputting the resized image.

55. The system of claim 54, further comprising a pre-compression post-resizing
image enhancement module for automatically applying at least one filter before
compressing the enhanced image.

10

56. The system of claim 54, further comprising a post-processor for post-processing
the enhanced image before compressing the enhanced image.

15

57. The system of claim 42, further comprising an input module for inputting the
input image and a set of parameters, the input module is capable of inputting multiple
system, user defined naming conventions for the output image as the set of parameters.

58. The system of claim 57, wherein the parameters define the number of the output
images.

20

59. The system of claim 57, wherein the parameters define resizing parameters.

60. The system of claim 57, wherein the parameters define compression parameters.

61. The system of claim 42, further comprising a viewer for viewing the enhanced
5 image before outputting.

62. The system of claim 42, wherein the input images are processed in a server
computer of a network system, an output destination for the output image is coupled to
the network system.

10

63. The system of claim 62, wherein the network system is Internet, whereby the
system is capable of being applied in an automated on-the-fly environment where
images are sent to the server computer via the Internet whereupon the images are
processed and transmitted to the output destination.

15

64. The system of claim 42, wherein the image analysis module analyzes the image
based on an image histogram.

65. The system of claim 42, wherein the image classification module classifies the
20 image based on a Weighted Means range, a Weighted Standard Deviation range, and a
Halve Value Position range of an image luminosity histogram.

66. The system of claim 42, wherein the image enhancement module includes a brightness filter.

5 67. The system of claim 42, wherein the image enhancement module includes a contrast filter.

68. The system of claim 42, wherein the image enhancement module includes a saturation filter.

10

69. The system of claim 42, wherein the image enhancement module includes a curve filter.

70. The system of claim 42, wherein the image enhancement module includes an
15 unsharp mask filter.

71. The system of claim 53, wherein the image compression module includes a JPEG compression.

20 72. The system of claim 52, wherein the image resizer resizes the image to a thumbnail size.

73. The system of claim 51, wherein the image pre-processor includes a brightness filter.

5 74. The system of claim 51, wherein the image pre-processor includes a contrast filter.

75. The system of claim 51, wherein the image pre-processor includes a saturation filter.

10

76. The system of claim 51, wherein the image pre-processor includes an unsharp mask filter.

15 77. The system of claim 56, wherein the image post-processor includes a brightness filter.

78. The system of claim 56, wherein the image post-processor includes a contrast filter.

20 79. The system of claim 56, wherein the image post-processor includes a saturation filter.

80. The system of claim 56, wherein the image post-processor includes an unsharp mask filter.

5 81. The system of claim 55, wherein the pre-compression post-resizing image enhancement module includes an unsharp mask filter.

82. An image processing system for automatically processing a series of input images without operator's intervention, comprising:

10 an image analysis module for automatically analyzing each of the input images;
an image classification module for automatically classifying the analyzed image;
an image compression module for automatically compressing the classified
image based on classification; and
an output module for outputting at least one compressed image.

15 83. The system of claim 82, wherein the output module outputs a plurality of enhanced images with different file types without re-analyzing and re-classifying the input image.

20 84. The system of claim 82, wherein the output module outputs a plurality of enhanced images with different file sizes without re-analyzing and re-classifying the

input image.

85. The system of claim 82, wherein the image analysis module, the image
classification module, the image compression module, and the output module process
5 the input image in real time on-the-fly.

86. The system of claim 82, wherein the image analysis module, the image
classification module, the image compression module, and the output module process
the input image in a batch mode.

10 87. The system of claim 82, wherein the image analysis module, the image
classification module, the image compression module, and the output module process
the input image in an embedded software.

15 88. The system of claim 82, wherein the image analysis module, the image
classification module, the image compression module, and the output module process
the input image in an embedded hardware.

89. The system of claim 82, wherein the image analysis module, the image
20 classification module, the image compression module, and the output module process
the input image in an embedded firmware.

90. The system of claim 82, wherein the image analysis module, the image classification module, the image enhancement module, and the output module apply an individual image enhancement independently to each of the input images.

5

91. The system of claim 82, further comprising a pre-processor for pre-processing the input image before analyzing and classifying the input image.

10 92. The system of claim 82, further comprising an image resizer for resizing the enhanced image before outputting the compressed image.

93. The system of claim 91, further comprising a pre-compression post-resizing image enhancement module for automatically applying at least one filter before
15 compressing the enhanced image.

94. The system of claim 92, further comprising a post-processor for post-processing the input image before compressing the enhanced image.

20 95. The system of claim 82, further comprising an input module for inputting the input image and a set of parameters, the input module is capable of inputting multiple

system, user defined naming conventions for output images as the set of parameters.

96. The system of claim 95, wherein the parameters define the number of the output images.

5

97. The system of claim 95, wherein the parameters define resizing parameters.

98. The system of claim 95, wherein the parameters define compression parameters.

10 99. The system of claim 82, further comprising a viewer for viewing the compressed image before outputting.

100. The method of claim 82, wherein the input images are processed in a server computer of a network system, an output destination for the output image is coupled to
15 the network system.

101. The method of claim 100, wherein the network system is Internet, whereby the system is capable of being applied in an automated on-the-fly environment where images are sent to the server computer via the Internet whereupon the images are
20 processed and transmitted to the output destination.

102. The system of claim 82, wherein the image analysis module analyzes the input image based on an image histogram.

103. The system of claim 82, wherein the image classification module classifies the
5 input image based on a Weighted Means range, a Weighted Standard Deviation range, and a Halve Value Position range of an image luminosity histogram.

104. The system of claim 82, wherein the image compression module includes a
10 JPEG compression.

105. The system of claim 92, wherein the image resizer resizes the image to a
thumbnail size.

106. The system of claim 91, wherein the image pre-processor includes a brightness
15 filter.

107. The system of claim 91, wherein the image pre-processor includes a contrast
filter.

20 108. The system of claim 91, wherein the image pre-processor includes a saturation
filter.

109. The system of claim 91, wherein the image pre-processor includes an unsharp mask filter.

5 110. The system of claim 94, wherein the image post-processor includes a brightness filter.

111. The system of claim 94, wherein the image post-processor includes a contrast filter.

10

112. The system of claim 94, wherein the image post-processor includes a saturation filter.

113. The system of claim 94, wherein the image post-processor includes an unsharp
15 mask filter.

114. The system of claim 93, wherein the pre-compression post-resizing image enhancement module includes an unsharp mask filter.

20 115. A computer program storage medium readable by a computing system and encoding a computer program of instructions for executing a computer process of

automatically processing a series of input images without operator's intervention, in
automatically processing each of the input images, the computer process comprising:

providing processing parameters;

automatically analyzing, classifying, and enhancing the input image without

5 operator's intervention; and

outputting at least one enhanced image.

116. A computer data signal embodied in a carrier wave readable by a computing
system and encoding a computer program of instructions for executing a computer

10 process of automatically processing a series of input images without operator's
intervention, in automatically processing each of the input images, the computer process
comprising:

providing processing parameters;

automatically analyzing, classifying, and enhancing the input image without

15 operator's intervention; and

outputting at least one enhanced image.

117. A computer program storage medium readable by a computing system and
encoding a computer program of instructions for executing a computer process of

20 automatically processing a series of input images without operator's intervention, in
automatically processing each of the input images, the computer process comprising:

providing processing parameters;
automatically analyzing and classifying the input image without operator's
intervention;
automatically compressing the image; and
5 outputting at least one compressed image.

118. A computer data signal embodied in a carrier wave readable by a computing
system and encoding a computer program of instructions for executing a computer
process of automatically processing a series of input images without operator's
10 intervention, in automatically processing each of the input images, the computer process
comprising:
providing processing parameters;
automatically analyzing and classifying the input image without operator's
intervention;
15 automatically compressing the image; and
outputting at least one compressed image.

ABSTRACT

Image processing system and method automatically process a series of input images without operator's intervention. Each of the input images is automatically analyzed, classified, enhanced and/or compressed. Individual image enhancement is applied to each of the input images independently. A plurality of enhanced and/or compressed images can be outputted without re-analyzing and re-classifying the input image. The processed images have a high compression to quality ratio, produce images having quality and visual characteristics as viewed by a human including image contrast, brightness, and sharpness as compared with the input image, while capable of reducing the amount of memory required for storing the output images. The image processing system and method can process the images in real time on-the-fly or in a batch mode, and can operate in a wire and/or wireless transmission environment or embedded in a hardware, firmware, or software which is embedded in another system or application. The system can be a stand-alone system or a server/client network system, etc.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




FIG. 5A




FIG. 5B


```

graph TD
    Start(( )) --> D1{Is the Mean <150?}
    D1 -- Yes --> D2{Is S.D. between 45-55?}
    D1 -- No --> D3{Is the Mean >200?}
    D2 -- Yes --> M1[CRV12, 2B, 5Sat 30% Mask]
    D2 -- No --> D4{Is Mean between 100-120?}
    D4 -- Yes --> M2[CRV12, 1B, 3Sat 30% Mask]
    D4 -- No --> D5{Is Mean between 121-130?}
    D5 -- Yes --> N1[30% Mask]
    D5 -- No --> D6{Is Mean <175?}
    D6 -- Yes --> X1[1B, 3C 3Sat 30% Mask]
    D6 -- No --> X2[CRV9, 2C 3Sat 30% Mask]
    D3 -- Yes --> D7{Is the Mean >220?}
    D7 -- Yes --> A1[30% Mask]
    D7 -- No --> D8{Is the S.D. over 60?}
    D8 -- Yes --> A2[3C 10Sat 20% Mask]
    D8 -- No --> D9{Is S.D. <40?}
    D9 -- Yes --> A3[CRV8, 30% Mask]
    D9 -- No --> 1b((1b))
    D4 --> D10{Is M-M >15?}
    D10 -- Yes --> D11{Is the Mean <17 5?}
    D11 -- Yes --> W1[CRV10, 3B, 2C 6Sat 30% Mask]
    D11 -- No --> W2[CRV10, 4B 4Sat 30% Mask]
    D10 -- No --> D12{Is the S.D. <40?}
    D12 -- Yes --> Z1[CRV11 5Sat 30% Mask]
    D12 -- No --> D13{Is the M-M >15?}
    D13 -- Yes --> Z2[2C 7Sat 30% Mask]
    D13 -- No --> Z3[-1B +4C 20% Mask]
    D13 --> Z4[-2B 3Sat 30% Mask]
    D13 --> Z5[ ]
    
```

FIG. 6B




Fig. 7A




Fig. 7C

United States Patent Application

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: SYSTEM AND METHOD FOR IMAGE PROCESSING

The specification of which

- a. ☐ is attached hereto
b. ☒ is entitled SYSTEM AND METHOD FOR IMAGE PROCESSING, and having **Attorney Docket No. 13095.1USU1**.
c. ☐ was filed on as application serial no. and was amended on (if applicable) (in the case of a PCT-filed application) described and claimed in international no. filed and as amended on (if any), which I have reviewed and for which I solicit a United States patent.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56 (attached hereto).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on the basis of which priority is claimed:

- a. ☒ no such applications have been filed.
b. ☐ such applications have been filed as follows:

FOREIGN APPLICATION(S), IF ANY, CLAIMING PRIORITY UNDER 35 USC § 119			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)
ALL FOREIGN APPLICATION(S), IF ANY, FILED BEFORE THE PRIORITY APPLICATION(S)			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)

I hereby claim the benefit under Title 35, United States Code, § 120/365 of any United States and PCT international application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below:

U.S. PROVISIONAL APPLICATION NUMBER	DATE OF FILING (Day, Month, Year)
60/184,088	22 February 2000

I hereby appoint the following attorney(s) and/or patent agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith:

Albrecht, John W.	Reg. No. 40,481	Leon, Andrew J.	Reg. No. P-46,869
Ali, M. Jeffer	Reg. No. 46,359	Leonard, Christopher J.	Reg. No. 41,940
Anderson, Gregg I.	Reg. No. 28,828	Liepa, Mara E.	Reg. No. 40,066
Batzli, Brian H.	Reg. No. 32,960	Lindquist, Timothy A.	Reg. No. 40,701
Beard, John L.	Reg. No. 27,612	Lycke, Lawrence E.	Reg. No. 38,540
Berns, John M.	Reg. No. 43,496	McAuley, Steven A.	Reg. No. 46,084
Black, Bruce E.	Reg. No. 41,622	McDonald, Daniel W.	Reg. No. 32,044
Branch, John W.	Reg. No. 41,633	McIntyre, Jr., William F.	Reg. No. 44,921
Bremer, Dennis C.	Reg. No. 40,528	Mitchem, M. Todd	Reg. No. 40,731
Bruess, Steven C.	Reg. No. 34,130	Mueller, Douglas P.	Reg. No. 30,300
Byrne, Linda M.	Reg. No. 32,404	Nichols, A. Shane	Reg. No. 43,836
Campbell, Keith	Reg. No. P-46,597	Pauly, Daniel M.	Reg. No. 40,123
Carlson, Alan G.	Reg. No. 25,959	Phillips, Bryan K.	Reg. No. P-46,990
Caspers, Philip P.	Reg. No. 33,227	Phillips, John B.	Reg. No. 37,206
Chiapetta, James R.	Reg. No. 39,634	Plunkett, Theodore	Reg. No. 37,209
Clifford, John A.	Reg. No. 30,247	Prendergast, Paul	Reg. No. 46,068
Daignault, Ronald A.	Reg. No. 25,968	Pytel, Melissa J.	Reg. No. 41,512
Daley, Dennis R.	Reg. No. 34,994	Qualey, Terry	Reg. No. 25,148
Dalglish, Leslie E.	Reg. No. 40,579	Reich, John C.	Reg. No. 37,703
Daulton, Julie R.	Reg. No. 36,414	Reiland, Earl D.	Reg. No. 25,767
DeVries Smith, Katherine M.	Reg. No. 42,157	Samuels, Lisa A.	Reg. No. 43,080
DiPietro, Mark J.	Reg. No. 28,707	Schmaltz, David G.	Reg. No. 39,828
Edell, Robert T.	Reg. No. 20,187	Schuman, Mark D.	Reg. No. 31,197
Epp Ryan, Sandra	Reg. No. 39,667	Schumann, Michael D.	Reg. No. 30,422
Glance, Robert J.	Reg. No. 40,620	Scull, Timothy B.	Reg. No. 42,137
Goggin, Matthew J.	Reg. No. 44,125	Sebald, Gregory A.	Reg. No. 33,280
Golla, Charles E.	Reg. No. 26,896	Skoog, Mark T.	Reg. No. 40,178
Gorman, Alan G.	Reg. No. 38,472	Spellman, Steven J.	Reg. No. 45,124
Gould, John D.	Reg. No. 18,223	Stoll-DeBell, Kirstin L.	Reg. No. 43,164
Gregson, Richard	Reg. No. 41,804	Sumner, John P.	Reg. No. 29,114
Gresens, John J.	Reg. No. 33,112	Swenson, Erik G.	Reg. No. 45,147
Hamer, Samuel A.	Reg. No. P-46,754	Tellekson, David K.	Reg. No. 32,314
Hamre, Curtis B.	Reg. No. 29,165	Trembath, Jon R.	Reg. No. 38,344
Harrison, Kevin C.	Reg. No. P-46,759	Tuchman, Ido	Reg. No. 45,924
Hertzberg, Brett A.	Reg. No. 42,660	Underhill, Albert L.	Reg. No. 27,403
Hillson, Randall A.	Reg. No. 31,838	Vandenburgh, J. Derek	Reg. No. 32,179
Holzer, Jr., Richard J.	Reg. No. 42,668	Wahl, John R.	Reg. No. 33,044
Johnston, Scott W.	Reg. No. 39,721	Weaver, Karrie G.	Reg. No. 43,245
Kadievitch, Natalie D.	Reg. No. 34,196	Welter, Paul A.	Reg. No. 20,890
Karjeker, Shaukat	Reg. No. 34,049	Whipps, Brian	Reg. No. 43,261
Kastelic, Joseph M.	Reg. No. 37,160	Whitaker, John E.	Reg. No. 42,222
Kettelberger, Denise	Reg. No. 33,924	Wickhem, J. Scot	Reg. No. 41,376
Keys, Jeramie J.	Reg. No. 42,724	Williams, Douglas J.	Reg. No. 27,054
Knearl, Homer L.	Reg. No. 21,197	Withers, James D.	Reg. No. 40,376
Kowalchyk, Alan W.	Reg. No. 31,535	Witt, Jonelle	Reg. No. 41,980
Kowalchyk, Katherine M.	Reg. No. 36,848	Wu, Tong	Reg. No. 43,361
Lacy, Paul E.	Reg. No. 38,946	Xu, Min S.	Reg. No. 39,536
Larson, James A.	Reg. No. 40,443	Zeuli, Anthony R.	Reg. No. 45,255

I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/ organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct Merchant & Gould P.C. to the contrary.

Please direct all correspondence in this case to Merchant & Gould P.C. at the address indicated below:

Merchant & Gould P.C.
P.O. Box 2903
Minneapolis, MN 55402-0903



I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

2	Full Name Of Inventor	Family Name RAMSAY	First Given Name Thomas	Second Given Name E
0	Residence & Citizenship	City Minneapolis	State or Foreign Country Minnesota	Country of Citizenship U.S.A.
1	Post Office Address	Post Office Address 5937 Dupont Avenue South	City Minneapolis	State & Zip Code/Country Minnesota 55419/USA
Signature of Inventor 201:				Date:
2	Full Name Of Inventor	Family Name RICHARDS	First Given Name Kenneth	Second Given Name W.
0	Residence & Citizenship	City Richfield	State or Foreign Country Minnesota	Country of Citizenship U.S.A.
2	Post Office Address	Post Office Address 7311 - 15th Avenue South	City Richfield	State & Zip Code/Country Minnesota 55423/USA
Signature of Inventor 202:				Date:
2	Full Name Of Inventor	Family Name WACKERFUSS	First Given Name Michael	Second Given Name K.
0	Residence & Citizenship	City St. Paul	State or Foreign Country Minnesota	Country of Citizenship U.S.A.
3	Post Office Address	Post Office Address 1748 Laurel Avenue	City St. Paul	State & Zip Code/Country Minnesota 55104/USA
Signature of Inventor 203:				Date:
2	Full Name Of Inventor	Family Name MURRAY	First Given Name Arnold	Second Given Name E.
0	Residence & Citizenship	City Chisago City	State or Foreign Country Minnesota	Country of Citizenship U.S.A.
4	Post Office Address	Post Office Address 10975 Stacy Trail	City Chisago City	State & Zip Code/Country Minnesota 55013/USA
Signature of Inventor 204:				Date:
2	Full Name Of Inventor	Family Name PETERSEN	First Given Name Philip	Second Given Name N.
0	Residence & Citizenship	City Plymouth	State or Foreign Country Minnesota	Country of Citizenship U.S.A.
5	Post Office Address	Post Office Address 3615 Union Terrace Lane	City Plymouth	State & Zip Code/Country Minnesota 55441/USA
Signature of Inventor 205:				Date:

§ 1.56 Duty to disclose information material to patentability.

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is canceled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

(1) prior art cited in search reports of a foreign patent office in a counterpart application, and

(2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

(1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim;

or

(2) It refutes, or is inconsistent with, a position the applicant takes in:

(i) Opposing an argument of unpatentability relied on by the Office, or

(ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

(1) Each inventor named in the application:

(2) Each attorney or agent who prepares or prosecutes the application; and

(3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.